

Negative Refraction Demultiplexer Metamaterial for millimeter waves

M. Navarro-Cia^a, M. Beruete^a, I. Campillo^b, and M. Sorolla^a

^a Millimeter Wave Laboratory, Universidad Pública de Navarra, Campus Arrosadia, 31006 Pamplona, Spain

^b CIC nanoGUNE Consolider, Paseo Mikeletegi 56, 301, 20009 Donostia, Spain

Abstract—In this work, by using an extraordinary transmission metamaterial prism and taking advance of its inherent dispersive behavior, the feasibility of manufacturing a multiplexer/demultiplexer at millimeter-wave is shown. Depending on the incoming beam frequency, the outgoing beam suffers a different deflection (governed by Snell's law). Since the frequency dependent index of refraction of this metamaterial can go from almost zero to -2 for the first propagation band, different negative outgoing angles can be obtained and then, diverse paths for each frequency, as the near-field experimental results confirm.

I. INTRODUCTION

THE millimeter-wave (mm-wave) range is a promising frequency band for the future but more and more actual broad band communications and a great effort toward millimeter-wave components is needed.

In the last decade, an exotic field called metamaterial [1], [2] has shaken the foundations of the electromagnetism due to the unusual and often not naturally-available electromagnetics properties of its structures. These newly accessible electromagnetic properties make these materials an excellent platform for demonstrating unique electromagnetic phenomena and constructing novel components. However, the losses are still a big issue in these structures.

The Millimeter Wave Laboratory has overcome this problem by taking advance of the Extraordinary Transmission phenomenon [3], [4]. By just close-stacking subwavelength hole pattern and stacked with a longitudinal periodicity $d_z = 1.5$ mm. The near-field transmission coefficient is measured by means of a AB-MillimetreTM millimeter wave vector network analyzer in the frequency range from 45 to 110 GHz, with the same experimental set-up used for the Fresnel zone measurements [7] (see Fig. 1).

Later on, it has reported many applications for this stacked structure as polarizer or lens [6] to name a few, which proves the viability of manufacturing components with this new technology.

II. RESULTS

The feasibility of the demultiplexing behavior of the ETM prism has been tested with the structure shown in Fig. 1. It consists of aluminum plates perforated with a double period subwavelength hole pattern and stacked with a longitudinal periodicity $d_z = 1.5$ mm. The near-field transmission coefficient is measured by means of a AB-MillimetreTM millimeter wave vector network analyzer in the frequency range from 45 to 110 GHz, with the same experimental set-up used for the Fresnel zone measurements [7] (see Fig. 1).

The experimental results shown in Fig. 2. corroborate the envisaged multiplexing behavior for 3 different frequencies.




Fig 1. Details of the experimental set-up. Top view of the prototype and schematic of structure with parameters, $a = 2.5$ mm, $d_x = 3$ mm, $d_y = 5$ mm, and $d_z = 1.5$ mm. The angle of the prism is 26.6 deg.




Fig 2. Normalized transmission coefficient vs. angle of refraction for 3 different frequencies.

ACKNOWLEDGEMENTS

This work has been supported by the Ministerio de Educación y Ciencia through the project TEC2005-06923-C03-01.

REFERENCES

- [1] V. G. Veselago, "The electrodynamics of substances with simultaneously negative values of ϵ and μ ," Sov. Phys. Uspekhi 10, 509-514 (1968).
- [2] J. B. Pendry, A. J. Holden, D. J. Robbins and W. J. Stewart, "Magnetism from conductors and enhanced nonlinear phenomena," IEEE Trans. Microwave Theory Tech. 47, 2075-2084 (1999).
- [3] Lewis, M. Isaacson, A. Harootunian, and A. Muray, "Development of a 500Å resolution microscope," Ultramicroscopy 13, pp. 227-231 (1984).
- [4] T. W. Ebbesen, H. J. Lezec, H. Ghaemi, T. Thio, and P. A. Wolf, "Extraordinary optical transmission through sub-wavelength hole arrays," Nature 391, pp. 667-669 (1998).
- [5] M. Beruete, M. Sorolla, and I. Campillo, "Left-handed extraordinary optical transmission through a photonic crystal of subwavelength hole arrays," Opt. Express 14, pp. 5445-5455, (2006).
- [6] M. Beruete, M. Navarro-Cia, M. Sorolla, and I. Campillo, "Polarized left-handed extraordinary optical transmission of subterahertz waves," Opt. Express 15, pp. 8125-8134, (2007).
- [7] M. Navarro-Cia, M. Beruete, M. Sorolla, and I. Campillo, "Polarized left-handed extraordinary optical transmission of subterahertz waves," Opt. Express 16, pp. 560-566, (2008).