

Quantum-Cascade Photonic Crystal Laser

A. Benz^a, G. Fasching^a, Ch. Deutsch^a, A. M. Andrews^a,
K. Unterrainer^a, P. Klang^b, W. Schrenk^b, G. Strasser^b

^a Vienna University of Technology, Photonics Institute and
Center of Micro- and Nanostructures, 1040 Vienna, Austria

^b Vienna University of Technology, Institute of Solid-State Electronics and
Center of Micro- and Nanostructures, 1040 Vienna, Austria

Abstract—The realization of terahertz (THz) quantum-cascade laser operating at photonic crystal modes is shown. The devices are showing stable single-mode operation under all driving conditions and a tuning range from 2.25 to 2.65 THz.

I. INTRODUCTION AND BACKGROUND

THE terahertz (THz) spectral region has drawn a lot of attention due to the large number of possible applications such as real-time imaging¹, heterodyne detection² or spectroscopy. These applications require high-power, narrow-band sources with a defined emission characteristic. Quantum cascade lasers (QCLs) are capable of delivering high output powers in this spectral region. However, it is important to find a way to precisely control the emission in terms of frequency and stability. Standard distributed-feedback lasers (DFBs) have shown their potential to solve some of these challenges³. Nevertheless, the use of 2-D photonic crystal (PhC) lasers should increase the performance further as their gain enhancement is predicted to be larger compared to 1-D DFBs⁴.

Here we present THz-QCLs which are lasing on true PhC-modes. Unlike in previous work^{5,6}, the PhC are not used as frequency selective mirrors but as the gain medium itself⁷.

II. RESULTS

The PhC used is built up by a triangular lattice of dielectric rods surrounded by air with a filling factor of 33 %. The rods are etched through the active region of the THz-QCL by reactive etching. Thereby, a vertical etching profile with smooth sidewalls is achieved. The 2-D crystal is embedded in a double-metal waveguide to prevent out-of-plane scattering. Thereby, we achieve a very high confinement for the optical mode. This allows us to realize devices with a side length of only 5 periods of the PhC, this corresponds to the free-space wavelength of approximately 100 μm .

The period of the PhC has been varied from 22 to 35 μm . The devices are lasing at the flat-band region at the K-point in the lowest band. Thereby, we are able to achieve stable single-mode emission under all driving conditions. These devices allow us to tune the emission from the gain maximum at 2.65 THz, measured at a Fabry-Perot resonator, to 2.25 THz. Spectra for two different periods are shown in Fig. 1. This gives us a 400 GHz tuning range, where the emission can be chosen without a regrowth of the sample. Despite the large tuning range, all devices are lasing at least up to liquid-

Nitrogen temperature in pulsed mode operation.

These devices have a large potential for applications due to the precise frequency selection, stable operating conditions, the huge tuning range and reasonably high operating temperatures.




Fig. 1. Spectra for PhC with a period of 22 and 31 μm respectively. The emission frequency is defined by the PhC itself. The inset is showing a schematic of the PhC with the main crystallographic directions.

REFERENCES

- [1] A. W. M. Lee, Q. Qin, S. Kumar, B. S. Williams, Q. Hu and J. L. Reno, "Real-time terahertz imaging over a standoff distance (>25 m)," *Appl. Phys. Lett.* **89**, 141125 (2006)
- [2] J. R. Gao, J. N. Hovenier, Z. Q. Yang, J. J. A. Baselmans, A. Baryshev, M. Hajenius, T. M. Klapwijk, T. O. Klaassen, B. S. Williams, Q. Hu and J. L. Reno, "Terahertz heterodyne receiver based on a quantum cascade laser and a superconducting bolometer," *Appl. Phys. Lett.* **86**, 244104 (2005)
- [3] L. Mahler, R. Köhler, A. Tredicucci, F. Beltram, H. E. Beere, E. H. Linfield, D. A. Ritchie and A. G. Davies, "Single-mode operation of terahertz quantum cascade lasers with distributed feedback resonators," *Appl. Phys. Lett.* **84**, 5446 (2004)
- [4] S. Nojima, "Optical-gain enhancement in two-dimensional active photonic crystals," *J. Appl. Phys.* **90**, 545 (2001)
- [5] A. Benz, G. Fasching, Ch. Deutsch, A. M. Andrews, K. Unterrainer, P. Klang, W. Schrenk and G. Strasser, "Terahertz photonic crystal resonators in double-metal waveguides," *Opt. Express* **15**, 12418 (2007)
- [6] L. A. Dunbar, V. Moreau, R. Ferrini, R. Houdré, L. Sirigu, G. Scalari, M. Giovannini, N. Hoyler and J. Faist, "Design, fabrication and optical characterization of quantum cascade lasers at terahertz frequencies using photonic crystal reflectors," *Opt. Express* **13**, 8960 (2005)
- [7] H. Zhang, L. A. Dunbar, G. Scalari, R. Houdré and J. Faist, "Terahertz photonic crystal quantum cascade lasers," *Opt. Express* **15**, 16818 (2007)